


- 1 RHEINZINK-Roof Drainage
  - a Gutter, half round
  - d Gutter bracket, clad with RHEINZINK
- 2 RHEINZINK-Double Standing Seam Roof
- 16 RHEINZINK-Building Profile
  - a Eaves flashing
  - f Base trim
  - j Fascia profile
- 18 Support Profile
  - a Galvanised steel
- 19 Separating Layer
  - a Structured underlay VAPOZINC®
- 20 Substructure
  - d Softwood boarding, non continuous
  - f OSB/ veneer plywood sheathing, thickness min. 22 mm,
- 21 Batten/ Squared Timber
  - Squared Timber
- 23 Supporting Structure
- 25 Thermal Insulation
  - c Linitherm thermal insulation panel with 22 mm OSB outer face, insitua foam to any cavities
- 27 Vapour Control Layer
  - b sd value > 100 m



## STANDARD DETAIL

Eave, Linitherm + Half round gutter + Bracket mounted	Title	Scale
		1:2
		Size
		A3
	Detail-Nr.	Drawn
	09020203021201000101_GB_en	WGM
		Date
		07.03.14

The detail describes an optional design in standard cases based on a European climate. Any user of this document is responsible to verify the feasibility of the solution with respect to the specific local situation and conditions. Using the documents provided by RHEINZINK is a service, which excludes liability for damages or claims of any kind. Contingent liability for malice or gross negligence is unaffected.