


- 4 RHEINZINK-Angled Standing Seam Facade
- 16 RHEINZINK-Building Profile
  - c Perforated strip,
  - k Window sill coping slope >3°
- 18 Support Profile
  - a Galvanised steel
  - b Aluminium
- 19 Separating Layer
  - a Structured underlay VAPOZINC
  - d Breather membrane
- 20 Substructure
  - h OSB/ veneer plywood sheathing, thickness min. 18 mm
- 21 Batten/ Squared Timber
  - Batten
  - Squared timber
- 23 Supporting Structure
- 24 Window Foil
- 25 Thermal Insulation
- 30 Ventilated Air Space



### STANDARD DETAIL

|                                |            |                  |
|--------------------------------|------------|------------------|
| Window Sill                    | Title      | Scale            |
| + Overhanging profile          |            | 1:2              |
| + Drip setback - flush to seam |            | Size<br>A3       |
| 09030303010121000001_GB_en     | Detail-Nr. | Drawn<br>gam     |
|                                |            | Date<br>18.02.14 |

The detail describes an optional design in standard cases based on a European climate. Any user of this document is responsible to verify the feasibility of the solution with respect to the specific local situation and conditions. Using the documents provided by RHEINZINK is a service, which excludes liability for damages or claims of any kind. Contingent liability for malice or gross negligence is unaffected.